

BW360

BW360 is a boiler water additive for preventing scale within steam boilers.

BW360 has been formulated to provide tolerance to a wide range of conditions and still prevent the formation of scale.

ADVANTAGES

Can prevent scale in the presence of hardness slippage due to softener malfunction.

- ◆ easy to control and test for product.
- ◆ prevents the formation of scale.
- ◆ can break up certain boiler deposit on line.
- ◆ low alkalinity content to allow for increased cycling within the boiler. This saves fuel.
- ◆ contains only ingredients for use where steam contacts food or foot products under the United States Food and Drug Administration regulations.

HOW MUCH TO USE

BW360 should be added to the feedwater to give a reserve in the boiler water of 30 to 60 ppm orthophosphate. The addition depends on the hardness present in the feedwater; as a guide, with 5 ppm hardness, about 30 mls/m³ is required. It is important that the OH alkalinity (2P-M) within the boiler is maintained at a minimum of 200 ppm to create a non-adherent sludge. If this level of alkalinity is not maintained, sticky sludge can be created which will risk scaling the boiler.

METHOD OF APPLICATION

BW360 should be dosed directly from the product container. It should be added on the basis of the amount of raw water make-up that is introduced to the boiler. The product should be dosed to the feedwater line as close to the boiler as is feasible. Alternatively, it can be dosed directly to the boiler.

BW360 should only be used where the feedwater hardness does not exceed 20 ppm.

PROPERTIES

Appearance:	Clear to pale pink liquid
Density:	1.1 -1.3
pH of 1% solution:	Approx. 7.0 – 7.2

HANDLING AND STORAGE

BW360 has a low toxicity but standard chemical precautions should be taken, however, when handling all chemicals. Wear gloves and goggles. Consult Health & Safety sheet for further information.

PACKAGING

BW360 is available in 25 litre and 200 litre containers.