

HYDRAGUARD LIMITED

RESINCARE

RESINCARE is a produced used to prevent iron fouling of water softener resin. Supply water to base exchange softeners often contain suspended organic matter and iron which can foul the resin bed in the exchange vessel. **RESINCARE** will help to keep the resin clear of such impurities and remove any suspended iron present in the supply water.

ADVANTAGES

- easy to use
- removes suspended iron
- low product odour

HOW MUCH TO USE

RESINCARE should be used on a preventative basis and added regularly to the brine tank, for example once a week, depending on the maintenance regime. Alternatively it may be added more frequently, say each time the softener is to be regenerated.

METHOD OF APPLICATION

RESINCARE should be added to the brine tank at a rate of 1 litre per 25 kilos of salt.

PROPERTIES

Appearance: Clear pale amber solution
Density: 1.0 – 1.1
PH of neat product: 6.0-8.0

HANDLING AND STORAGE

RESINCARE has a low toxicity but standard chemical precautions should be taken when handling all chemicals. Wear gloves and goggles. Consult Health and Safety sheet for further information.

PACKAGING

RESINCARE is available in 25 litre containers.

PRODUCT DATA

Hydraguard Limited
Rose Croft
Newton on Rawcliffe
Pickering
North Yorkshire YO18 8QE

Tel No. 01751 475964